

ROYALE PLAY MARMO

Water-Based Marble Stucco

DESCRIPTION & USES

- **ROYALE PLAY MARMO** is a high quality acrylic paste for Marble effect decorative finish.
- Produces Vapor Breathable, smooth, hard, durable, polished surface for interior.
- Machine tintable formulation, therefore available in variety of colors.
- Excellent workability, easy application, high covering and economic.
- Fast setting properties enables to finish the job in one day.
- High resistance to soap and water clean up.
- Water based environment friendly product.

PROPERTIES

Finish	Smooth, Marble like sheen
Color	Machine Tintable to wide range of colors
Density at 25°C	Approx 1.65 kg/ lit.
Washability/ Wet Scrubbing	Washable after full cure and polishing
Diluent/Thinner	Water
Drying Time at 25°C and relative humidity 50%	<ul style="list-style-type: none"> • Touch Dry : 1 hour • Recoat : 4-6 hours

INSTRUCTIONS FOR USE

1) Surface preparation:

- Surface must be clean, free from oil, grease, dirt, loose paint and any other foreign materials.
- Old painted surfaces should be cleaned first from all loose paint and other contaminants that can affect adhesion.

2) Application:

- Use **SEALCOAT** with suitable dilution to prepare the surface.
- Apply **UNOSHIELD/ACRYPUTTY** to make the surface smooth.
- Follow with another coat of **SEALCOAT**.
- Apply uniform coat of **ROYALE PLAY MARMO** by trowel to make an undercoat.
- Take small amount of **ROYALE PLAY MARMO** on trowel and apply in patches on base coat.
- Remove excess quantity by trowel.
- Repeat applying patches vertically and horizontally until the surface is fully covered.
- When surface become tack free, flatten the surface by smooth edge of trowel till marble effect finish is obtained.
- For elegant marble finish, apply multiple layers and flatten the surface
- Finally wax polish may be applied to improve stain resistance.

APPLICATION TOOLS

Trowel, Putty knife.

COVERAGE

About 4-6 m²/Kg per coat for base coat. For subsequent coats, it is 5 - 8 m²/Kg. However it depends on way of application and surface conditions.

PACKAGING

Refer to company price list or contact the local representative.

STORAGE & SHELF- LIFE

18 months in original tightly closed containers away from direct sunlight and excessive heat.

Refer safety data sheet before using the product